

## CAMEC FOUR SEASONS HATCH



This hatch has features to make it the most versatile and easy to use hatch on the market. Opening from all 4 sides, with fully removable flyscreens for ease of cleaning or replacement, easy to open and close, can be left partly open while out of the caravan for the day, allowing airflow into your caravan while having no concerns of water getting in through the hatch if it rains.

### Features:

- Modern looking
- One piece moulded body
- Opens on all 4 sides
- Removable flyscreens
- Large control knobs for ease of use
- Exceeds gas regulation requirement 220scm
- Easy to fit
- Fits old four seasons hatch cutout
- Supplied with wind deflector
- Supplied with screws and foam tape for fitting
- Internal trim available
- Spare parts available

DESCRIPTION	PART NO.
Camec 4 Seasons Hatch	039585
Internal Trim 50mm	039927

CARTON QTY	BARCODE
1	9339051001881

### Technical specifications:

Dimensions -	
Installed Height:	130mm
Overall:	720mmW x 720mmD
Cut out:	660mm x 660mm
Weight:	3.25kg
Continuous Airflow:	220cm <sup>2</sup>



## CAMEC FOUR SEASONS HATCH

Camec's New 4 Season's Hatch exceeds 220 square CM of permanent open area. This exceeds the Australian Gas Installation requirements of, 210 square centimetres permanent open area, for all Caravans over 6 metres (internal length of caravan).

Australian Standard AS5601-2004 Gas Installations; clause 6.2.7 (c) refers to table 6.3. Table 6.3 states; required Air Supply to Flued Appliances Installed in a Caravan = minimum 210 square centimetres total free ventilation area (permanent open area) is required in the upper level. The ventilation (permanent open area) is to be within 300 mm of the highest part of the ceiling or roof, for all Caravans over 6 metres long (internal length). Therefore: 1-only Camec New 4 Seasons Hatch @ 220 square centimetres permanent open area, requires no further added ventilation to comply with AS5601-2004 Gas Installations.

